1711053-1

Copper Cable, category 6, 4 pair duplex, UTP, LSZH, 23 AWG solid, 500 m reel, white

Product Classification

Regional Availability EMEA

Portfolio NETCONNECT®

Product Type Twisted pair cable

General Specifications

ANSI/TIA Category 6

Cable Component Type Horizontal

Cable Type U/UTP (unshielded)

Conductor Type, singles

Conductors, quantity

Backet Color

Pairs, quantity

Solid

White

Transmission Standards ANSI/TIA-568-C.2 | CENELEC EN 50288-6-1 | ISO/IEC 11801 Class E

Dimensions

 Cable Length
 1640 ft | 499.872 m

 Diameter Over Jacket, nominal
 0.512 in | 13.005 mm

Conductor Gauge, singles 23 AWG

Electrical Specifications

Operating Voltage, maximum 80 V

Remote PoweringFully complies with the recommendations set forth by IEEE 802.3bt (Type 4) for the safe delivery

of power over LAN cable when installed according to ISO/IEC 14763-2, CENELEC EN 50174-1,

CENELEC EN 50174-2 or TIA TSB-184-A

Material Specifications

Conductor MaterialBare copperInsulation MaterialPolyolefin

Jacket Material Low Smoke Zero Halogen (LSZH)

Environmental Specifications



1711053-1

EN50575 CPR Cable EuroClass Dca | a1 | d2 | s2

Packaging and Weights

Packaging Type Reel

Regulatory Compliance/Certifications

Agency Classification

CENELEC EN 50575 compliant, Declaration of Performance (DoP) available

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant

