



TRIAX

connecting the future



IFP 124 PSU 2 out 24V/200mA

Article number: 339124

Product description:

TRIAX power supplies in elegant design.

F-connector on all inputs. Simple and easy installation. The 2 outputs are equipped with auto-terminated F connector meaning that there is no need to terminate an un-used output.

- 24V DC 200mA
- 1 input, 230V AC
- 1 x RF F-connector input
- 2 x RF auto-terminated F-connector outputs for 2 x TV sets.
- Signal insertion loss: 4dB.
- Quick and easy installation
- Install instruction already available on UFO 150/170 box and manual
- Single packed in compact color retail cardboard box.

Specifications

ORDER INFORMATION

EAN Number	5702663391246
------------	---------------

CHARACTERISTICS

Type	Power supply
------	--------------

FREQUENCY	
Frequency range	47...862 MHz
LOSS	
Through loss	4.0 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
AC Supply voltage	100...240 VAC
PSU output DC voltage	24 VDC
PSU output max. DC current	200 mA
CONNECTORS	
Connector Type	F-female
Number of inputs	1
Number of outputs	2
MECHANICAL	
Packaging Height	0,070 m
Packaging Width	0,110 m
Packaging Depth	0,150 m
Packaging Volume	0,001 m ³
Net Weight	0,315 kg
Tara Weight	0,030 kg
Total Weight	0,345 kg