

LazrSPEED® 550 WideBand LC to Unconnectorized, Fiber Pigtail, 0.9 mm Riser - SBJ

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®
Ordering Note	For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration

General Specifications

Color, connector A	Beige
Construction Type	Simplex pigtail
Interface, Connector A	LC/UPC
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	2.00 lb @ 90 ° 5.00 lb @ 0 °
--	--------------------------------

Optical Specifications

Fiber Type	OM5, LazrSPEED® wideband
Insertion Loss, maximum, connector A	0.3 dB
Return Loss, minimum, connector A	27 dB

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Low Smoke Zero Halogen (LSZH) Riser

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

