


NPC6AUZDB-WT



NPC RJ45 Patch Cord, category 6A, Unshielded, LSZH, White

- High-performance patch cords exceeding industry standards supporting NETCONNECT channel specifications
- Standardized transparent, slim-line boots provides consistent patch cord appearance and supports highest density applications
- Colored clips are available to fit the transparent boot, eliminating the need of multiple colors for matching every jacket color
- Colored pull latch tabs are available for easier plug release handling from the modular jack

Product Classification

Regional Availability	EMEA
Portfolio	NETCONNECT®
Product Type	Twisted pair patch cord
Product Series	NPC

General Specifications

ANSI/TIA Category	6A
Cable Type	U/UTP (unshielded)
Conductor Type	Solid
Interface, Connector A	RJ45 plug
Interface Feature, connector A	Standard
Interface, Connector B	RJ45 plug
Interface Feature, connector B	Standard
Jacket Color	White
Pairs, quantity	4
Wiring	T568B

Dimensions

Cable Assembly Length, minimum (ft)	3
Cable Assembly Length, maximum (ft)	100
Cable Assembly Length, minimum (m)	1
Cable Assembly Length, maximum (m)	30
Diameter Over Jacket	7.24 mm 0.285 in

NPC6AUZDB-WT

Compatible Conductor Gauge, solid

24 AWG

Ordering Tree

NPC -

Jacket Color

10	BK	Black
	BL	Blue
	GN	Green
	GY	Gray
	OR	Orange
	PK	Pink
	RD	Red
	VT	Violet
	WT	White
	YL	Yellow

UOM

11	F	Foot
	M	Meter
	N	Inch
	C	Centimeter

Length

12 XXX

Notes

- Cords > 1m are authorized for use in channels and are an effective standalone method used to connect active devices
- Cords < 1m are also valid elements for use in a channel or as an equipment interconnect but due to their limited length are not guaranteed to meet component compliance requirements that were developed to assess the quality of longer cords

Mechanical Specifications

Plug Insertion Life, minimum

750 times

Environmental Specifications

Operating Temperature

-20 °C to +60 °C (-4 °F to +140 °F)

Relative Humidity

Up to 93%, non-condensing

Environmental Space

Low Smoke Zero Halogen (LSZH)

Safety Standard

UL 1863

Packaging and Weights

Packaging quantity

1

Included Products

2843018-3 – Integrated Boot and Pair Manager for MP-6AU, size 71, transparent
MP-6AU-Boot-71-1

6-2843008-1 – Modular Plug, Category 6A/6, Unshielded, Cond Insulation OD - 0.79mm, 100 pcs
MP-6AU-Plug-B-1

CC884014144/BU – CC6AZH Category 6A U/UTP Cable, non-plenum, white jacket, 4 pair count, bulk length,
CC6AZH WHT C6A 4/24 SO U/UTP RL reel
BULK