


## RKUB (Loudspeaker cable)



### Speaker cable

Max conductor temperature: -25°C/+70°C  
Voltage Rating: 60 V

### Application

RKUB is a PVC insulated cable that are used as loudspeaker cable or for signaling applications.

### Standards

Conductor: IEC 60228,5  
Insulation: EN 50363,4-1  
Construction: SS-ISO 6722-1:2011  
Flame retardant: IEC 60332-1

### Construction

Conductor	Flexible, plain or tinned copper class 5
Insulation	PVC
Colour	ex. White, Black, Customers choice
Packing	ex. Coil, Bobbin, Customers choice

Type Code	Cross-section [mm <sup>2</sup> ]	Insulation thickness [mm]	Outer diameter [mm]	Copper weight [kg/km]	Packing
RKUB 2X0,5	0,5	0,5	h:1,9 w:3,8	2 X 4,8	Customers choice
RKUB 2X0,75	0,75	0,6	h:2,3 w:4,4	2 X 7,2	Customers choice
RKUB 2X1,5	1,5	0,6	h:2,8 w:5,7	2 X 14,4	Customers choice
RKUB 2X2,5	2,5	0,6	h:3,2 w:6,5	2 X 24	Customers choice
RKUB 2X4	4	0,6	h:3,8 w:7,8	2 X 38,4	Customers choice
RKUB 2X6	6	0,6	h:4,4 w:9,0	2 X 57,6	Customers choice