

Cat. 6 4x2x23/1 AWG U/UTP Indoor/Outdoor FR-LSZH/FR-LSZH

Part Number: **750UZ04101**

- Applications:** High bandwidth digital applications with low BER, Indoor/Outdoor use, fixed installations, Low temperature Indoor/Outdoor applications
- General Construction:** 4 Unshielded Twisted Pairs (UTP), with a special star shaped central filler cabled together and double jacketed with a special FR-LSZH compounds with a rip cord between the jackets.
- Outer Jacket Material:** FR-LSZH
- Outer Diameter:** 8.3 mm nom.
- Weight:** 79 kg/km
- Total Copper Weight:** 52.4 kg/cable km



Design & Materials

Detailed Construction:

Cable voltage rate is 300 V, however the cable is not intended to supply mains electric supply. It may be used in installations and applications where 300 V supply and equipment are installed.

Both inner cable and complete cable complies with the CPR D_{CA} rating.

Conductor Material:	Annealed Bare Copper
Conductor Size:	23 AWG
Conductor Size:	0.58 mm
Conductor Construction:	Solid
Insulation Material:	Solid PO
Insulation O.D.:	1.0 mm nom.
Conductor unit identification:	Solid/stripe
Color Code:	Per TIA/EIA 568-B
Inner Jacket Material:	LSZH
Inner Jacket Diameter nom.:	6.7 mm nom
Inner Jacket Color:	Light Gray - or per request
Outer Jacket Color:	Black
Marking:	Per request, Teldor Standard

Standards

Applicable Standards:	IEC 61156, ISO/IEC 11801-1, TIA/EIA-568, RoHS 3 2015/863/EU
Flammability Rating:	IEC 60332-1, EN 50575:2014 D _{ca} s2d2a1 (CPR)

Electrical Properties:

Cat. 6 Un-screened Pair Horizontal Cables*

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 6	Typical Value	Cat. 6	Typical Value	Cat. 6	Typical Value	Cat. 6	Typical Value	Cat. 6	Typical Value	Cat. 6
1	2.0	2.8	75.0	72.3	78.0	75.3	22.0	20.0	90.0	65.0	93.0	68.0
4	3.7	3.8	66.0	63.3	69.0	66.3	25.0	23.0	90.0	53.0	93.0	56.0
10	5.7	6.0	60.0	57.3	63.0	60.4	28.0	25.0	80.0	45.0	83.0	48.0
20	8.1	8.5	56.0	52.8	59.0	55.8	28.0	25.0	80.0	39.0	83.0	42.0
30	10.0	10.5	53.0	50.1	56.0	53.1	27.0	23.8	70.0	35.5	73.0	38.5
100	19.0	19.9	45.0	42.3	48.0	45.3	24.0	21.1	63.0	25.0	66.0	28.0
150	23.6	24.9	43.0	39.7	46.0	42.7	22.0	18.8	60.0	21.5	63.0	24.5
200	27.7	29.1	41.0	37.8	44.0	40.8	21.0	18.0	58.0	19.0	61.0	22.0
250	31.4	33.0	38.0	36.3	41.0	39.3	20.0	17.3	55.0	17.0	58.0	20.0

*Supplied cables meet the minimum Cat. 6 transmission requirements as per **IEC 61156-5 Ed. 2**

Performance

Frequency Range:	1 - 400 MHz
Impedance:	100 Ω
Coupling Attenuation:	Type III
Max. DC Resistance :	72 Ω/km@20°C
Max. Resistance Unbalance:	2 %
Capacitance:	56 pF/m
Capacitance Unbalance:	1.2 pF/m max.
Velocity of Propagation:	68 % nom.
Propagation Delay Skew:	35 ns/100m max.
Dielectric Strength:	700 V/minute
Min. Insulation Resistance :	5 GΩ•km
Voltage Rating:	300 V
Min. Bend Radius:	120 mm
Max. Operating Temperature:	+70 °C
Min. Operating Temperature:	-55 °C

Prepared By	Revised By	Version Num	Modified on
Jacov Ben-Ary	Ofer Solter	2.5	09-11-2020

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd.