

Cat.7 4x2x23/1AWG S/FTP CSA Direct Burial PE

Part Number: **9928659xxx**

Applications:	High bandwidth digital applications with low BER, Low temperature, outdoor fixed installations, Outdoor and direct burial installations
General Construction:	The cable consist of 4 individually aluminum-foil shielded twisted pairs, an overall tinned copper braid, inner LSZH jacket, water blocking tape, CSA (Corrugated Steel Armor) and outer UV resistant PE jacket.
Outer Jacket Material:	PE
Outer Diameter:	12.0 mm nom.
Weight:	154 kg/km



Design & Materials

Detailed Construction:

Note: flammability rating refer to the internal cable only.

Conductor Material:	Annealed Bare Copper
Conductor Size:	23 AWG
Conductor Size:	0.58 mm
Conductor Construction:	Solid
Insulation Material:	Cellular PO
Insulation O.D.:	1.35 mm nom.
Conductor unit identification:	Solid Color
Color Code:	Per TIA/EIA 568-B
Ind. Shield Material:	Aluminum/Polyester Foil
Ind. Shield Design:	Helically applied Aluminum foil, 100% coverage
Conductor unit lay-up:	Pairs
Drain-wire 2 Construction:	Solid
Drain-wire 3 Construction:	Solid
Overall Shield Design:	Braid
Overall Shield Material:	Tinned-copper braid
Overall Braid Shield:	Yes
Overall Braid Material:	Annealed Tinned Copper
Braid Coverage:	50 % nom.
Overall Drain-wire Material:	Annealed Tinned Copper
Overall Drain-wire Construction:	Solid
Inner Jacket Material:	FR-LSZH
Inner Jacket Diameter nom.:	7.4 mm nom
Inner Jacket Color:	Per request
2nd Inner Jacket Material:	HFFR
Armoring:	Corrugated Steel
Outer Jacket Color:	Black
Marking:	Per request, Teldor Standard

Standards

Applicable Standards:	IEC 61156, ISO/IEC 11801, RoHS-2 2011/65/EU
Flamability Rating:	IEC 60332-1

Electrical Properties:
Cat. 7 Horizontal Cables *

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.0	2.0	105.0	99.4	108.0	102.4	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	3.6	3.7	98.0	90.4	101.0	93.4	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	5.6	5.8	95.0	84.4	98.0	87.4	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	7.9	8.3	90.0	80.0	93.0	83.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	9.7	10.2	85.0	77.2	88.0	80.2	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	18.0	19.0	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	22.4	23.6	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	26.0	27.5	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	29.4	31.0	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	32.5	34.2	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	38.0	40.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9
500	43.0	45.2	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	47.6	50.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4

*Supplied cables meet the minimum Cat. 7 transmission requirements as per IEC 61156-5 Ed. 2

Performance

Frequency Range:	1 - 600 MHz
Impedance:	100
Coupling Attenuation:	Type I
Max. DC Resistance :	73 /km@20°C
Max. Resistance Unbalance:	2 %
Capacitance:	46 pF/m
Capacitance Unbalance:	1.3 pF/m max.
Velocity of Propagation:	78 % nom.
Propagation Delay Skew:	30 ns/100m max.
Dielectric Strength:	700 V/minute
Dielectric Strength to Shield:	700 V/minute
Min. Insulation Resistance :	4 G •km
Tensile Strength - Short Term:	350 N max.
Min. Bend Radius:	250 mm
Max. Operating Temperature:	+65 °C
Min. Operating Temperature:	-45 °C
UV resistance:	Yes

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.