

Conoral data

Technical datasheet for:

ADSB Set and ADSB-D Set





General data			
Item	Sealing element with protection bend (-double) Set		
Package unit	10 Pcs.		
	House connection for a speedpipe-ground Ø7x1.5 through a coredrilling Ø28mm or a sleeve SKW 32		ADSB 28/7 Set
	House connection for a speedpipe-ground Ø7x1.5 or a cable (Ø 7.0-9.0mm) through a coredrilling Ø47mm or a sleeve SKW 50		ADSB 7.0-9.0 Set
	House connection for a speedpipe-ground 10x2.0 (12x2.0) or a cable (Ø 9.0-12.5mm) through a coredrilling Ø47mm or a sleeve SKW 50		ADSB 9.0-12.5 Set
	House connection double for a speedpipe-ground 7x1.5 and/or cable (Ø 7.0-9.0mm) through a coredrilling Ø47mm or a sleeve SKW 50		ADSB-D 7.0-9.0 Set
	House connection double for a speedpipe-ground 10x2.0 (12x2.0) and/or cable (Ø 9.0-12.5mm) through a coredrilling Ø47mm or a sleeve SKW 50		ADSB-D 9.0-12.5 Set
Technical data			
Quality	Value	Unit	
Material	Acrylnitril-Butadien-Styrol ABS		
Tight against non pressing water	1	bar	
Fire behavior of lever	F - d2		

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

E - d2

Ε

The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH Am Schaidweg 7 94559 Niederwinkling GERMANY

(DIN EN 13501-1)

pressure disc (DIN EN 13501-1)

Fire behavior of cover and

Tel. +49 9962 950-200 Fax +49 9962 950-202 info@gabocom.com www.gabocom.com Editor: LF Release: MK Date: 07.12.2015

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.