


Technical datasheet for:

## DSM indoor



### General data


<b>Item</b>	Connector indoor
<b>Description</b>	The halogenfree and flame retardant connector DSM indoor is suitable for connecting speedpipe-indoor for indoor use. It is pressure-tight up to 15 bar, resistant to tensile and easy to install. The fire behavior of the hard component is classified according to DIN EN 13501-1.
<b>Package unit</b>	50 Pcs. (Ø4, Ø5, Ø7, Ø10); 25 Pcs. (Ø12, Ø14)

### Technical data

Quality	Value	Unit
<b>Material</b>		
<b>Material</b>	Polyamid PA flame retardant	
<b>Halogenfree (DIN EN 60684-2)</b>	< 0,02	%
<b>Fire behavior (DIN EN 13501-1)</b>	B s2 d0	

Technical datasheet for:

**DSM indoor**



**Products**

<b>Dimension</b>	DSM 4 i:	d = 11; L = 30	mm
	DSM 5 i:	d = 12; L = 32	
	DSM 7 i:	d = 13; L = 32	
	DSM 10 i:	d = 18; L = 42	
	DSM 12 i:	d = 22; L = 46	
	DSM 14 i:	d = 24; L = 47	
<b>Pressure</b>	0.5 (permanent gas- and watertight)		bar
	15 / 30		bar / min
<b>Burst pressure</b>	min. 30		bar
<b>Tensile strength</b>	DSM 4 i:	min. 100	N
	DSM 5 i:	min. 125	
	DSM 7 i:	min. 200	
	DSM 10 i:	min. 400	
	DSM 12 i:	min. 450	
	DSM 14 i:	min. 500	
<b>Conduit systems for cable management (EN 61386-22)</b>	passed		

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001. The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
info@gabocom.com  
www.gabocom.com

Editor: AF  
Release: MK  
Date: 24.06.2016  
Edition: 5

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.