


Technical datasheet for:

EZA-t 7


General data

Item	Divisible sealing element
Description	The divisible and tensile sealing elements EZA-t are reusable and suit for sealing empty and occupied speedpipe. Before 10 bar of blow-in pressure are reached, the integrated safety valve opens.
Package unit	40 Pcs.

Technical data

Quality	Value	Unit
Material	PolyPhenylenOxid PPO	
Dimension	d = 21; L = 43	mm
Sealing range (short term)	EZA-t 7 / 0.8-2.5	mm
	EZA-t 7 / 2.0-4.0	
Pressure	0.5	bar
Tensile strength of speedpipe	min. 70	N
Tensile strength to micro-cabel (Ø4.0mm)	min. 20	N
Loading capacity of connecting clamps	min. 750	N
Fire behavior of case half and clamp (DIN EN 13501-1)	E - d2	

gabocom ist nach dem Qualitätssicherungssystem DIN EN ISO 9001, dem Umweltmanagementsystem DIN EN ISO 14001 und dem Energiemanagementsystem DIN EN ISO 50001 zertifiziert. Die verwendeten Materialien erfüllen die REACH-Vorgabe (EU-Verordnung 1907/2006) und die RoHS-Vorgabe (EU-Richtlinien 2011/65).

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 GERMANY

Tel. +49 9962 950-200
 Fax +49 9962 950-202
 info@gabocom.com
 www.gabocom.com

Editor: LF
 Release: MK
 Date: 03.12.2015
 Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.