


Technical datasheet for:

## RSM transparent permanent



### General data

<b>Item</b>	Reducer transparent permanent
<b>Description</b>	The transparent, permanent reducers RSM are used for the gas- and water-tight connection of speedpipe with the same inner diameter up to 15 bar. They can easily and fastly be installed. By removing the locking ring they can easily be disengaged. The fittings are applicable for direct burying.
<b>Package unit</b>	25 Pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>	PolyAmid PA	
<b>Dimension</b>	RSM 10/7:	d = 18; L = 35
	RSM 12/10:	d = 22; L = 46
	RSM 14/12:	d = 24; L = 47
	RSM 16/14:	d = 26; L = 48
<b>Pressure</b>	0,5 (permanent gas- and watertight)	
	15 / 30	bar / min
<b>Burst pressure</b>	min. 30	bar
<b>Tensile strenght</b>	RSM 10/7:	min. 200
	RSM 12/10:	min. 400
	RSM 14/12:	min. 450
	RSM 16/14:	min. 500
<b>Fire behavior of corpus (DIN EN 13501-1)</b>	E - d2	

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.**

**The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

**Meet the requirements of EN 50411-2-8:2009.**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
info@gabocom.com  
www.gabocom.com

Editor: LF  
Release: MK  
Date: 03.12.2015  
Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.