


Technical datasheet for:

SKW



General data

Item	Sleeve	
Description	The sanded sleeves SKW are used for being plastered in brick walls. The fittings are protected against contamination when being plastered.	
Package unit	SKW 32:	18 Pcs.
	SKW 50:	8 Pcs.

Technical data

Quality	Value		Unit
Material	PolyVinylChlorid - Unplastinized PVC-U		
Dimension	SKW 32:	d = 32; L = 390	mm
		d = 32; L = 500	
	SKW 50:	d = 50; L = 390	
		d = 50; L = 500	
Pressure	0.5		bar

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001. The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
GERMANY

Tel. +49 9962 950-200
Fax +49 9962 950-202
info@gabocom.com
www.gabocom.com

Editor: LF
Release: MK
Date: 07.12.2015
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.