


Technical datasheet for:

speed•pipe[®] 7x0.75 CE



General data

Item	speedpipe 7x0.75
Description	speedpipe for the use in cable ducts
Production length on spool (1200x370mm)	5000m
Weight	approx. 0.016 kg/m
Total weight	approx. 110 kg (including spool)

Technical data

Quality	Value	Unit
Material		
Material	PolyEthylen PE	
MFI (according to DIN 8075)	max. 30	%
Homogeneity	free from inclusions < 0.02	mm ²
Internal pressure creep rupture test (DIN 16874)	Sigma 4.0 for 170h at 80°C	N/mm ²
Fire behavior (DIN EN 13501-1)	E	
speedpipe 7x0.75		
Dimension	$D = 7.0^{+0.1}; s = 0.75^{+0.1}$	mm
Colour of stripes	red, green, blue, yellow, white, grey, orange, violet, brown and black opposite transparent windows	
Pressure nominal	PN 10	
Inner surface	35 optimized sliding ribs	
Burst pressure	min. 30	bar at 20°C
Max. recommended tensile strength	120	N at 20°C
Tensile strength at break	230	N at 20°C

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
GERMANY

Tel. +49 9962 950-200
Fax +49 9962 950-202
info@gabocom.com
www.gabocom.com

Editor: LF
Release: MK
Date: 02.12.2015
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.