

Technical datasheet for:

Markerpeg Typ: MPeg-T



General data

Item	Markerpeg
Description	The marker should be placed along the track or at a breakout that needs to be found. The markerpeg should be put vertically in the ground. It can be mounted with the included holder to the duct or microduct. Detection range: Vertical 1,5-2m; 45°-1m
Package unit	10 Pcs.

Technical data

Quality	Value	Unit
Material	PP, Ferrite, Silicone, MKP, Copper	
Length	100	mm
Diameter	21	mm
Weight	30	g
Frequency	101,4 (Telecom)	kHz
Installation	vertical	
Temperature range	-10 - +25	°C
Colour	orange	

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65)

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
Germany

Phone 0049 (0)9962 950 200
Fax 0049 (0)9962 950 202
info@gabocom.de
www.gabocom.de

Editor: AF
Release: MK
Date: 19.09.2017
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.