Product Specifications





Broadband Solutions

F677 TSE APD SM MT Black

75 Ohm Coaxial Drop Cable, Series 6, black PE jacket, flooded for underground

Construction Materials

Corrosion Protection APD Amorphorus Polypropolene

Center Conductor Material Copper-clad steel

Dielectric Material Foam PE
Inner Shield (Braid) Coverage 77 %
Inner Shield (Braid) Gauge 34 AWG
Inner Shield (Braid) Material Aluminum

Inner Shield (Tape) Material Aluminum/Polymer/Aluminum (APA) bonded

Jacket Material PE

Outer Shield (Tape) Material Aluminum/Polymer/Aluminum (APA)

Dimensions

Diameter Over Center Conductor, nominal 1.016 mm | 0.040 in
Diameter Over Dielectric, nominal 4.572 mm | 0.180 in
Diameter Over Inner Shield (Tape), nominal 4.750 mm | 0.187 in
Diameter Over Jacket, nominal 7.061 mm | 0.278 in
Jacket Thickness, nominal 0.7620 mm | 0.0300 in

Shipping Weight 33.00 lb/kft

Electrical Specifications

dc Resistance, Inner Conductor, nominal 30.50 ohms/kft dc Resistance, Outer Conductor, nominal 6.40 ohms/kft dc Resistance, Loop, nominal 36.90 ohms/kft

dc Resistance Note Nominal values based on a standard condition of 20 °C (68 °F)

Capacitance 53.1 pF/m | 16.2 pF/ft

Characteristic Impedance 75 ohm
Characteristic Impedance Tolerance ±3 ohm
Nominal Velocity of Propagation (NVP) 85 %

Environmental Specifications

Environmental Space Buried

General Specifications

Cable Type Series 6

Packaging Type 305 meter wooden reel

Shield Construction Type Trishield
Center Conductor Gauge 18 AWG
Center Conductor Type Solid
Jacket Color Black
Jacket Marking Meters

Product Specifications



4814103 | F677TSEF SM MT

Warranty One year

Electrical Performance

Frequency	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	
5 MHz	1.90	0.58	
55 MHz	5.25	1.60	
83 MHz	6.40	1.95	
187 MHz	9.35	2.85	
211 MHz	10.00	3.05	
250 MHz	10.82	3.30	
300 MHz	11.64	3.55	
350 MHz	12.63	3.85	
400 MHz	13.61	4.15	
450 MHz	14.43	4.40	
500 MHz	15.29	4.66	
550 MHz	16.08	4.90	
600 MHz	16.73	5.10	
750 MHz	18.54	5.65	
865 MHz	20.01	6.10	
1000 MHz	21.49	6.55	

^{*} Attenuation listed represents maximum values at standard condition of 20 °C (68 °F)

Regulatory Compliance/Certifications

AgencyRoHS 2002/95/EC

Classification
Compliant

ISO 9001:2008 Designed, manufactured and/or distributed under this quality management system