

ECS- Fiber Optic Panel 19" 1HE



ECS sliding empty chassis panel system in its basic form is supplied with the removable SC Duplex front plate unloaded without adapters ready for you to install the adapter of your choice.

The tray is locked in place with two plastic latches after the removable front plate is mounted, when fully extended the tray is designed to lower to 45°. This provides the perfect working platform for simple installation or easy maintenance and access even after the panel is installed in the rack.

Features/Benefits

- ▶ Recessed panel mounting option
- ▶ Accept any type of removable front plate
- ▶ Detachable rear plate for larger cable entry
- ▶ No exposed screws
- ▶ 45° working angle
- ▶ High quality finish, no sharp edges
- ▶ 4 rear cable entries (2x PG16 , 2x PG13.5)

- ▶ Environmentally friendly materials & packaging

Technical Characteristics

PARAMETER	VALUE
Height	1U (44.4mm)
Width	482mm
Depth	205mm
Net weight	2.3kg
Packaged weight	2.6kg
Packaged dimensions	530mmx250mm x45mm (WxDxH)
Suitable adapter type	All types
Mounting adjustment range	50mm
Rear cable port Φ 25mm	2
Rear cable port Φ 20mm	2
Material	Cold Rolled Steel
Material thickness	1.2mm
Material coating	Powder Coating
Standard color	Black RAL 9004
Operating temperature	-40°C to + 60°C
Compliant to	RoHS,Reach / SvHC

Ordering Information

PART NO	DESCRIPTION
ECS24500DW	Sliding Empty Chassis Panel,Unloaded