

ECS Patch cord U/UTP category 6_A halogen free

Part number	Description
GC6AU0,5/WH	ECS patch C6A U/UTP 0,5 meter LSZH
GC6AU1,0/WH	ECS patch C6A U/UTP 1,0 meter LSZH
GC6AU1,5/WH	ECS patch C6A U/UTP 1,5 meter LSZH
GC6AU2,0/WH	ECS patch C6A U/UTP 2,0 meter LSZH
GC6AU3,0/WH	ECS patch C6A U/UTP 3,0 meter LSZH
GC6AU5,0/WH	ECS patch C6A U/UTP 5,0 meter LSZH
GC6AU7,5/WH	ECS patch C6A U/UTP 7,5 meter LSZH
GC6AU10,0/WH	ECS patch C6A U/UTP 10,0 meter LSZH

Standard color: White

Other lengths are available upon request

Description

Unshielded patch cords in halogen free category 6_A performance for indoor use. Patch cords are 100% performance tested and wired T568B; constructed of 24 AWG stranded, UTP copper cable and modular plugs for superior performance; nominal cable diameter is 6.0mm.

Standards

The cables performance complies with category 6_A requirements according ISO / IEC 11801 and EN50173-1

Dimensions

Conductor: 24 AWG

Cable diameter: nom. 6,0mm

Temperature requirements

During installation: 0 till 50 C°

Operating: -20 C° till 60 C°

Fire rating

IEC 60332-1



Cat.6
A-