

760238083 | DM12-24LC-SM-ULL



G2 ULL Singlemode MPO-12 Distribution Module, 2x12F MPO unpinned to 24F LC Blue with internal shutters, Method B Enhanced

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber module
Product Brand	SYSTIMAX ULL TeraSPEED®
Product Series	G2

General Specifications

Adapters, quantity, front	24
Adapters, quantity, rear	2
Color, front	Blue
Color, rear	Gray
Data Module Type	Standard
Interface, front	LC
Interface Feature, front	Standard
Interface, rear	MPO Unpinned
Interface Feature, rear	Key up/up
Polarity	Method B Enhanced
Shuttered	Yes
Total Fibers, quantity	24
Total Ports, quantity, front	24

Dimensions

Height	26.42 mm 1.04 in
Width	96.52 mm 3.8 in

760238083 | DM12-24LC-SM-ULL

Depth 117.35 mm | 4.62 in

Optical Specifications

Fiber Type G.657.A2

Insertion Loss, maximum 0.6 dB

Environmental Specifications

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard CE | CSA | UL

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

Classification

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant

