

Dura End Cap



PRODUCT DESCRIPTION

Used to temporarily seal MicroDuct ends during transportation or storage

APPLICATION AREA

For use with MicroDucts in direct-buried or sub-duct installations

MAIN CHARACTERISTICS

Material

Body:	Polyvinylchloride (PVC)
-------	-------------------------

Temperature

Transport and Storage:	-20 °C to +60 °C
------------------------	------------------

Operation:	-20 °C to +60 °C
------------	------------------

Installation:	-15 °C to +45 °C
---------------	------------------

Others

UV-Resistant:	No
---------------	----

Operational lifetime:	2 years
-----------------------	---------

TECHNICAL DATA SHEET: ACCESSORIES

PRODUCT VARIATIONS

Material Description	Length (mm)	ID (mm)	OD (mm)	Packaging (pcs)	SAP code
DuraEnd Cap 4 mm	15	3.6	6.2	100	20040057
DuraEnd Cap 5 mm	15	4.5	7	100	20040040
DuraEnd Cap 6 mm	20	5.5	8	100	20073050
DuraEnd Cap 7 mm	20	6	8.9	100	20020042
DuraEnd Cap 10 mm	20	9	12	100	20020043
DuraEnd Cap 12 mm	20	11	15	100	20020044
DuraEnd Cap 14 mm	25	13	17.4	100	20020045
DuraEnd Cap 16 mm	25	15	17.5	100	20020062
DuraEnd Cap 18 mm	30	17	19.5	100	20040080
DuraEnd Cap 20 mm	25	19	22	100	20020228