

## MIM 16-00 Extension module for MIE 8-00 or MIE 16-00

- ✓ Extension to additional 512 input streams and additional 16 DVB-C or 12 DVB-T output channels

### Order information



Type	MIM 16-00
Order no.	MIM01600
GTIN	7611682007275
PE	1
VE	1
EU customs tariff number	85176990



### Technical data

#### IPTV input

Supported input transport streams	SPTS, MPTS (CBR/VBR)
Max. number (out of SPTS or MPTS)	512
Supported protocols	IP V4; UDP; RTP; IGMP v2, v3
Total net data rate	1 × 900 Mbps
Transportstreams	

Modifiable program information	Program name, SID remapping, PID filtering, TSID, ONID
PCR correction	automatic, adaptive, <500 ns
LCN	Yes
NIT handling @ DVB-C	auto   manual   off
EPG regeneration	Yes
Encryption	LG ProIdiom   Samsung LYNK   AES 128   DVB-CSA*
Output	

Number of channels	1 × 16 DVB-C 1 × 12 DVB-T
Frequency range	109...1006 MHz @ DVB-C 109...862 MHz @ DVB-T
Channels selectable	S2...K87 @ DVB-C S2...K69 @ DVB-T
Channel bandwidth	7 MHz, 8 MHz
Possible frequency shift	-4...+4 MHz (0.5 MHz steps)
Connector	1 × F-female
Test port	1 × F-female (-30 dB)
Impedance	75 Ω
Output level adjustable	80...105 dBμV @ DVB-C 77...102 dBμV @ DVB-T

Output modulation	
Compliance	EN 50083-9   ETSI TS 101 154   ETSI EN300 429   ETSI EN 300 744   ITU-T J.83A/C
Type	QAM32, QAM64, QAM128, QAM256 @ DVB-C QPSK, QAM16, QAM64 @ DVB-T
Supported output formats	MPEG-2/H.262, MPEG-4/H.264 and HEVC/H.265
MER	≥ 40 dB @ DVB-C ≥ 36 dB @ DVB-T
BER	≥ 9x10 <sup>-9</sup>
Roll off	15 %
Shoulder attenuation	≥ 56 dB
C/N	≥ 45 dB
Reflection	> 14 dB
Bit rate, max	50,87 Mbps @ DVB-C 31,668 Mbps @ DVB-T

FFT	2K mode @ DVB-T
FEC	1/2, 2/3, 3/4, 5/6, 7/8 @ DVB-T
Guard interval	1/4, 1/8, 1/16, 1/32 @ DVB-T
Symbol rate	1...7,5 MBauds/s
<b>Interfaces</b>	
IPTV input	1 x RJ45
CAS/IPTV (redundant)	1 x RJ45
Compliance IPTV/CAS interfaces	IEEE 802.3, 1000 Base-T (GigE)
Configuration/CAS	1 x RJ-45
Compliance configuration interface	IEEE 802.3, 10/100 Base-T
Software control and upgrading	Via Remote Access
Supported configuration protocols	HTTP, SNMP v1, SNMP, v2c, AXING SMARTPortal**
<b>General</b>	
Operating temperature range (acc. to EN 60065)	-10°C...+50°C
Storage temperature range (acc. to EN 60065)	-20 °C...+80 °C
Weight	0,516 kg
Comments	* available later ** encrypted, cloud-based application for configuration, monitoring and remote maintenance

## Example of use

