


Technical datasheet for:

C-Box



General data

Item	Cable-Box	
Description	The C-Box will be used to protect overlength of micro-cables in manholes.	
Package unit	1 Pcs.	
Transport and storage temperature	-40 to +65	°C
Laying or installation temperature	-10 to +50	°C
Operating temperature	-40 to +65	°C

Technical data

Quality	Value	Unit
Material	Acrylnitril-Butadien-Styrol ABS	
Dimension	Type A:	L = 600; B = 300; H = 120
	Type B:	L = 650; B = 680; H = 160

Assignment example

Assignment for cables with Ø6.5mm	Type A:	30	m
	Type B:	120	

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.
The used materials meet the REACH default (EU regulation 1907/2006).

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 GERMANY

Tel. +49 9962 950-200
 Fax +49 9962 950-202
 info@gabocom.com
 www.gabocom.com

Editor: CBR
 Release: MK
 Date: 24.10.2023
 Edition: 5

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.