


Technical datasheet for:

EBM-R


General data

Item	Repairing-sleeves
Description	Sleeve to repair light damages of occupied and unoccupied ducts.
Package unit	6 Pcs.

Technical data

Quality	Value		Unit
Material	PolyVinylChlorid - Unplastinized PVC-U		
Dimension	EBM-R 32:	d = 32; L = 261	mm
	EBM-R 40:	d = 40; L = 261	
	EBM-R 50:	d = 50; L = 261	
Pressure	0.5 (permanent gas- and watertight)		bar
Tensile strength	EBM-R 32:	min. 1300	N
	EBM-R 40:	min. 1300	
	EBM-R 50:	min. 1500	
Pressing operation clamp on case	min. 1550		N

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 GERMANY

Tel. +49 9962 950-200
 Fax +49 9962 950-202
 info@gabocom.com
 www.gabocom.com

Editor: SV
 Release: MK
 Date: 30.07.18
 Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.