


Technical datasheet for:

EZA-t 20



General data

| | |
|---------------------|--|
| Item | Divisible sealing element |
| Description | The divisible and tensile sealing elements EZA-t are reusable and suit for sealing empty and occupied speedpipe. Before 10 bar of blow-in pressure are reached, the integrated safety valve opens. |
| Package unit | 20 Pcs. |

Technical data

| Quality | Value | Unit |
|--|----------------------|------|
| Material | PolyPhenylenOxid PPO | |
| Dimension | d = 47; L = 51 | mm |
| Sealing range (short term) | EZA-t 20 / 5.0-6.5 | mm |
| | EZA-t 20 / 6.5-8.0 | |
| | EZA-t 20 / 8.0-10.5 | |
| | EZA-t 20 / 10.5-13.0 | |
| Pressure | 0.5 | bar |
| Tensile strength of speedpipe | min. 200 | N |
| Tensile strength to micro-cabel (Ø13.0mm) | min. 95 | N |
| Loading capacity of connecting clamps | min. 1550 | N |
| Fire behavior of case half and clamp (DIN EN 13501-1) | E - d2 | |

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
GERMANY

Tel. +49 9962 950-200
Fax +49 9962 950-202
info@gabocom.com
www.gabocom.com

Editor: AF
Release: MK
Date: 22.07.2020
Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.