


Technical datasheet for:

## EZA-t tc



### General Data

<b>Item</b>	Divisible sealing element for SRV-G tc	
<b>Description</b>	The reusable EZA-t tc are suitable for sealing tc-speedpipe bundles (tight covered) without loose outer jacket and up to 0.5 bar pressure tight.	
<b>Package unit</b>	12 Pcs.	
<b>Transport and storage temperature</b>	-40 to +65	°C
<b>Laying or installation temperature</b>	+5 to +40	°C
<b>Operating temperature</b>	-10 to +50	°C

### Technical Data

Quality	Value	Unit
<b>Material</b>	PolyVinylChlorid - Unplastinized PVC-U	
<b>Dimension</b>	L = 72	mm
<b>Pressure</b>	0.5	bar
<b>Pressure after 5 installations</b>	0.5	bar
<b>Tensile strength of speedpipe bundles</b>	250	N
<b>Tensile strength of micro tubes</b>	≥ 50	N
<b>Pressing operation clamp on case</b>	min. 1550	N
<b>Fire behavior of case half (DIN EN 13501-1)</b>	E	
<b>Fire behavior of clamp (DIN EN 13501-1)</b>	E - d2	

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.**

**The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
[info@gabocom.com](mailto:info@gabocom.com)  
[www.gabocom.com](http://www.gabocom.com)

Editor: CBR  
Release: MK  
Date: 05.05.2023  
Edition: 4

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.