


Technical datasheet for:

**EZA-t 40 / K**



### General data

Item	Divisible sealing element - EZA-t 40 / K	
Description	For sealing of cable ducts to 0.5 bar, reusable.	
Cable diameter	Cable outside diameter from 10.5mm up to 25.5mm.	
Package unit	12 Pcs.	
Transport and storage temperature	-40 to +65	°C
Laying or installation temperature	+5 to +40	°C
Operating temperature	-10 to +50	°C

### Technical data

Quality	Value	Unit
Material	PolyVinylChlorid - Unplastinized PVC-U	
Dimension	d = 40; L = 72	mm
Pressure	0.5	bar
Pressure after 5 installations	0.5	bar
Tensile strength on PE-Duct	min. 1000	N
Pressing operation clamp on case	min. 1550	N
Fire behavior of case half (DIN EN 13501-1)	E	
Fire behavior of clamp (DIN EN 13501-1)	E - d2	

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.**

**The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
info@gabocom.com  
www.gabocom.com

Editor: CBR  
Release: MK  
Date: 03.05.2023  
Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.