

Technical datasheet for:

**IB 7**



### General data

<b>Item</b>	Indoor bend 7 / IB 7
<b>Description</b>	The Indoor Bend IB 7 is used to redirect a speedpipe-indoor Ø7mm without damaging. The product is designed for operating temperatures of 0 - 50 °C for storage and installation.
<b>Optional</b>	An unlimited number of IB 7 can be stacked together.
<b>Package unit</b>	10 Pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>		
<b>Material</b>	Polyamid PA flame retardant	
<b>Halogenfree (DIN EN 60684-2)</b>	< 0,02	%
<b>Fire behavior (DIN EN 13501-1)</b>	B s2 d0	
<b>Product</b>		
<b>Dimension</b>	L = 110; B = 75; h = 125	mm
<b>Conduit systems for cable management (EN 61386-22)</b>	passed	

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.  
The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
info@gabocom.com  
www.gabocom.com

Editor: AF  
Release: MK  
Date: 20.02.2019  
Edition: 5

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.