


speed•pipe[®]-indoor 10x1.0 (€ <a href="https://www.eps.com/yellows




General data			
Item	speedpipe-indoor 10x1.0 (non-flam	speedpipe-indoor 10x1.0 (non-flame propagating)	
Description	speedpipe-indoor for the application inside buildings, drains or tunnels		
Weight	approx. 0.030 kg/m		
Production length	Spool	Total weight	
500m	700x370mm	approx. 28 kg (incl. spool)	
2500m	1200x370mm	approx. 103 kg (incl. spool)	
Min. bending radius (according to DIN EN 61386-22)	R = 10x speedpipe outer diameter Bending radiuses reduce the blowing in length		

Technical data				
Quality	Value	Unit		
Material Material				
Material	PolyEthylen PE, flame retardant			
MFI (according to DIN 8075)	max. 30	%		
Homogeneity	free from inclusions < 0.02	mm ²		
Halogenfree (DIN EN 60684-2)	< 0.02	%		
speedpipe-indoor 10x1.0				
Dimension	$D = 10.0^{+0.1}$; $s = 1.0^{+0.1}$ mm			
Colour	white (without colour addition)			
Pressure nominal	PN 10			
Inner surface	63 optimized sliding ribs			
Burst pressure	min. 20	bar at 20°C		
Max. recommended tensile strength	200	N at 20°C		
Tensile strenght at break	400	N at 20°C		
Fire behavior (DIN EN 13501-1)	D s3 d2			
Fire test (DIN EN 60332-1-2)	passed			
Riser Cable Routing Assembly (UL 2024)	passed			

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.



speed•pipe[®]-indoor 10x1.0 (€ <a href="https://www.eps.com/vision



Classification		
Classification code DIN EN 61386-22 (VDE 0605 Teil 22)	2-2-2-3-2-0-0-0-1-0	


Use accord	ding to DIN VDE 0100-520:2013-06 / IEC 6036	64-5-52:200	9-10
		allowed	not allowed
Installation	Unprotected installation (on plaster)	x	
in the building	Underground installation (screed)		x
	Laid in concrete		x
	Laid in hollow wall / wood (flammable materials)	x	
	Laid in plaster	x	
	Laid in structural cavities	x	
	Laid in suspended ceilings	x	
	Ceiling installation (installation distance < 0.80m)	x	

The direct installation of speedpipe-indoor in the ground is not permitted!

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.



speed•pipe®-indoor 10x1.0 (€ VDE-REG.-Nr. 8747
UL Listed E514120



CE - Declaration of Conformity		
1.0 Product Type:	speed•pipe-indoor (Microduct)	
1.1 Article Number:	3504 & 3505	
.2 Usage: LWL Protection tube for laying in the house		
2.0 Trade Name:	speed•pipe-indoor / Dimension 10 x 1.0 mm	
2.1 Manufacturer:	gabo Systemtechnik GmbH, Am Schaidweg 7, 94559 Niederwinkling	
3.0 Statement by the Manufacturer:	The issuance of this declaration of conformity takes place in own responsibility.	
4.0 Subject:	The traceability is ensured by the caption of the speed•pipe-indoor (Microduct).	

5.0 The Testing Institute VDE Offenbach (EU-ID-Nr. 0366)

has a Certified Nr.: 40039546 with production control exposed,

the above article was tested add to lean on with DIN EN 61386-22 (VDE 0605 Teil 22).

The relevant EU harmonization requirements are fulfilled



speed•pipe[®]-indoor 10x1.0 (€ VDE-REG.-Nr. 8747 UL Listed E514120



6.0 Harmonised Standards		
Main features	Classification	Technical Specification
Pressure load	Class 2	DIN EN 61386 VDE 0605 Teil 22
Impact strength	Class 2	DIN EN 61386 VDE 0605 Teil 22
Minimum Temperature Range	Class 2	DIN EN 61386 VDE 0605 Teil 22
Maximum Temperature Range	Class 2	DIN EN 61386 VDE 0605 Teil 22
Fire behavior	Class D (s3 d2)	DIN EN 13501-1

Niederwinkling the, 16.02.2015

beformares of

Klostermaier Stephan

CE - Conformity Commissioner of Business Management

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the Reach default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

The light transmittance of > 60% (low smoke) has been confirmed in accordance with DIN EN 61034-2 at the dimension 10x1.0.

gabo Systemtechnik GmbH Am Schaidweg 7 94559 Niederwinkling GERMANY Tel. +49 9962 950-200 Fax +49 9962 950-202 info@gabocom.com www.gabocom.com Editor: CKS
Release: MK
Date: 29.11.2021
Edition: 9

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.