

Technical datasheet for:



RAd-t 110 / 2x50(40)

General data

Item	Duct adapter	
Description	The divided duct adaptors RAd-t out of PE are used in sockets with a diameter of 110mm.	
Package unit	20 Pcs.	
Transport and storage temperature	-40 to +65	°C
Laying or installation temperature	-10 to +50	°C
Operating temperature	-40 to +65	°C

Technical data

Quality	Value	Unit
Material	PolyEthylen PE	
Dimension	D = 110; L = 63	mm
Connection area	D = 110	mm
Fire behavior (DIN EN 13501-1)	E	

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.
The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
 Am Schaidweg 7
 94559 Niederwinkling
 GERMANY

Tel. +49 9962 950-200
 Fax +49 9962 950-202
 info@gabocom.com
 www.gabocom.com

Editor: CBR
 Release: MK
 Date: 08.05.2023
 Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.