


Technical datasheet for:

HRMA



General data

Item	Split duct tee, divided
Description	By means of the divided split duct socket tee HRMA speedpipe or cables of a PE/PVC duct can be branched off safely and gas- and water-tight up to 0.5 bar.
Package unit	6 Pcs.

Technical data

Quality	Value		Unit
Material	PolyVinylChlorid - Unplastinized PVC-U		
Dimension	32/32-30°:	d1 = 32; d2 = 32; L = 261	mm
	40/40-90°:	d1 = 40; d2 = 40; L = 261	
	50/50-30°:	d1 = 50; d2 = 50; L = 261	
	50/50-90°:	d1 = 50; d2 = 50; L = 261	
Pressure	0.5		bar
Tensile strength	32/32-30°	min. 1300	N
	40/40-90°:	min. 1300	
	50/50-30°:	min. 1500	
	50/50-90°:	min. 1500	
Pressing operation clamp on case	min. 1550		N

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001. The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
GERMANY

Tel. +49 9962 950-200
Fax +49 9962 950-202
info@gabocom.com
www.gabocom.com

Editor: LF
Release: MK
Date: 07.12.2015
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.