


Technical datasheet for:

**SHi**


### General data

Item	Stiffener for inside		
Description	For inside application for speedpipe-bundle SRV / SRV-G to be inserted in the coat-duct before mounting the sealing element EZA-t.		
Package unit	SHi 40, SHi 50 and SHi 63:	12 Pcs.	
	SHi 32:	24 Pcs.	
Transport and storage temperature	-40 to +65	°C	
Laying or installation temperature	-10 to +50	°C	
Operating temperature	-40 to +65	°C	

### Technical data

Quality	Value		Unit
Material	PolyPhenylenOxid PPO		
Dimension	SHi 32:	d = 31; L = 70	mm
	SHi 40:	d = 39; L = 70	
	SHi 50:	d = 49; L = 70	
	SHi 63:	d = 62; L = 70	

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.**

**The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
info@gabocom.com  
www.gabocom.com

Editor: CBR  
Variant  
Date: 09.05.2023  
Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.