


Technical datasheet for:

SRV-M



General data

Item	Connector Box	
Description	Sleeve to repair light damages of occupied and unoccupied ducts.	
Package unit	10 Pcs.	
Transport and storage temperature	-40 to +65	°C
Laying or installation temperature	+5 to +40	°C
Operating temperature	-10 to +50	°C

Technical data

Quality	Value		Unit
Material	PolyVinylChlorid - Unplastinized PVC-U		
Dimension	SRV-M 40:	d = 40; L = 455	mm
	SRV-M 50:	d = 50; L = 455	
Pressure	0,5		bar
Tensile strength of the coating pipe of the SRV-G	SRV-M 40:	550	N
	SRV-M 50:	700	
Pressing operation clamp on case	min. 1550		N

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

gabo Systemtechnik GmbH
Am Schaidweg 7
94559 Niederwinkling
GERMANY

Tel. +49 9962 950-200
Fax +49 9962 950-202
info@gabocom.com
www.gabocom.com

Editor: CBR
Variant
Date: 09.05.2023
Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.