

# SAFETY-TECHNICAL INFORMATION



1 av 1

## JETTING MICRO DUCT LUBE

**MICRO DUCT LUBE** is a special lubricant for ducts up to 12 mm inside diameter, used previous to blowing of mini/micro fibre/cables.

**MICRO DUCT LUBE** is water based and can be used down to -15 degrees C. It leaves a very tiny film of lubricant, reduces drastically the friction, static electricity, and adheres perfectly to the fibre/cable and to the duct surface.

### Use:

1. Clean the inside of the duct by blowing a sponge slowly thru the duct.
2. Shake the bottle before using.
3. Pre lubricate by:
  - Place a sponge as far into the duct according to the table on the bottle.
  - Fill the suggested lubricant into the duct.
  - Place one or two sponges in the end and blow this thru slowly.
  - For best result, leave the lubricate to dry for 5- 10 min
4. The duct is now ready for fibre / cable blowing.

### Quantities:

15 ml x 1.000 mt for diameter 12 mm (about 15 cm full Duct)

10 ml x 1.000 mt for diameter 8 mm (about 20 cm full Duct)

5 ml x 1.000 mt for diameter 4 mm (about 30 cm full Duct)

### Technical Specifications:

Aspect	White liquid tiny viscosity
Odour	characteristic
Viscosity	30 sec. Ford cup diam. mm 4 at 20C°
Specific gravity	1,030 +- 0,03 gr/cm3
pH	7,5 +- 0,5
Inflammability	non infiammabile
Temperature	-15° + 70° C.
Biodegradability	yes
Toxic	The product is not toxic.
HS Code	3403.9900
Country of origin	Italy
Art. No	34030

JETTING AB, Sweden,  
[www.jetting.se](http://www.jetting.se)