


Technical datasheet for:

## EBM 32, 40 und 50



### General data

<b>Item</b>	Divisible connector
<b>Description</b>	Divisible connectors are used for the gas- and watertight sealing of connections between split duct (KKHR) and PE-duct.
<b>Package unit</b>	12 Pcs.

### Technical data

Quality	Value		Unit
<b>Material</b>	PolyVinylChlorid - Unplastinized PVC-U		
<b>Dimension</b>	EBM 32:	d = 32; L = 125	mm
	EBM 40:	d = 40; L = 125	
	EBM 50:	d = 50; L = 125	
<b>Pressure</b>	0.5 (permanent gas- and watertight)		bar
	10 / 30		bar / min
<b>Tensile strength</b>	EBM 32:	min. 1300	N
	EBM 40:	min. 1300	
	EBM 50:	min. 1500	
<b>Pressing operation clamp on case</b>	min. 1550		N

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001. The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
info@gabocom.com  
www.gabocom.com

Editor: LF  
Release: MK  
Date: 07.12.2015  
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.