


Technical datasheet for:



## EZA-t 10 indoor

### General data

Item	Divisible sealing element indoor
Description	The halogenfree, flame retardant, divisible and tensile sealing element EZA-t indoor is reusable suits for sealing occupied and unoccupied speedpipe for inhouse use. The EZA-t have a safety valve, which opens before reaching 10 bar of blow-in pressure. The fire behavior of the hard component is classified according to DIN EN 13501-1.
Package unit	40 Pcs.

### Technical data

Quality	Value	Unit
<b>Material</b>		
Material	Polyamid PA flame retardant	
Halogenfree (DIN EN 60684-2)	< 0,02	%
Fire behavior (DIN EN 13501-1)	B s2 d0	
<b>Product</b>		
Dimension	d = 27; L = 43	mm
Sealing range (short term)	EZA-t 10 / 1.8-3.5 indoor	mm
	EZA-t 10 / 3.0-5.0 indoor	
	EZA-t 10 / 5.0-6.5 indoor	
Pressure	0.5	bar
Tensile strength of speedpipe	min. 100	N
Tensile strength to micro-cabel (Ø6,5mm)	min. 50	N
Loading capacity of connecting clamps	min. 750	N
Conduit systems for cable management (EN 61386-22)	passed	

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.**

**The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
info@gabocom.com  
www.gabocom.com

Editor: AF  
Release: MK  
Date: 24.06.2016  
Edition: 3

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.