

DLT-090-192 - Dry Loose Tube G.657A

Part Number: **FA1921608E**

Applications: CATV and DataCom, Direct burial, General purpose indoor/outdoor LAN, Long Distance OSP

General Construction: This gel free cable contains 192 SM G657A1 Ultra color-coded optical fibers in 16 color-coded loose tubes. These tubes include a swellable yarn to prevent the ingress of water and are SZ stranded in two layers (5+11) around a dielectric central strength member. Waterblocking fiber-glass strength yarns reinforce the cable core and an outer jacket completes the cable design.

Outer Jacket Material: FR-LSZH

Outer Diameter: 15.5 mm nom.

Weight: 215 kg/km



Design & Materials

Buffer Material:	HFFR
Tube Diameter:	2.5 mm nom.
Color Code:	Per TIA/EIA 598-D
Central Strength Member:	FRP
Cabling:	SZ
Strength Elements:	E-Glass Yarns
Fiber Containing Tubes:	16
Total Number of Elements:	16
Number of fibers:	192
Waterblocking:	Dry Waterblocking
Rip-Cord:	Yes
Outer Jacket Color:	Green
Marking:	Teldor Standard

Standards

Applicable Standards:	IEC 60794-1-21/22, IEC 60794, ISO/IEC 11801-1, TIA/EIA-568, ASTM G154, RoHS 3 2015/863/EU
Flammability Rating:	IEC 60332-1, IEC 60332-3, IEC 60754-2, IEC 60754-1/2, IEC 60754, IEC 60754-1, IEC 61034, IEC 61034-1/2, EN 50575:2014 Dcas1d1a1 (CPR)

Performance

Max. Installation Tensile Load :	2700 N max.
Max. fiber strain at MIT:	0.6 %
Max. Residual Tension (MRS) :	810 N max.
Max. Fiber Strain at MRS.:	0.2 %
Impact Resistance:	10 N*m
Impact Resistance:	3 cycles
Max. Crush Resistance:	400 N/cm
Min. Bend Radius for Installation:	20xD mm
Min. Bend Radius for Operation:	10xD mm
Repeated Bending:	25 cycles
Torsion (L=125 x d):	10 cycles
Max. Operating Temperature:	+75 °C
Min. Operating Temperature:	-40 °C
Max. Installation Temperature:	+60 °C
Min. Installation Temperature:	-30 °C
Max. Storage Temperature:	+75 °C
Min. Storage Temperature:	-40 °C
UV Resistance:	Yes
Waterblocking:	Yes