

DLT-500-96/OM4 Dry Loose Tube

Part Number: **F30960815Z**


Applications: CATV and DataCom, Direct burial, General purpose indoor/outdoor LAN, Long Distance OSP

General Construction: This gel free cable contains 96 MM OM4 color-coded optical fibers in 8 color-coded FR polypropylene loose tubes. These tubes include a swellable yarn to prevent the ingress of water and are SZ stranded around a dielectric central strength member. Waterblocking fiber-glass strength yarns reinforce the cable core and an outer jacket completes the cable design.

Outer Jacket Material: FR-LSZH

Outer Diameter: 12.5 mm nom.

Weight: 137 kg/km



Design & Materials

Tube Diameter:	2.5 mm nom.
Color Code:	Per TIA/EIA 598-C
Central Strength Member:	FRP
Cabling:	SZ
Strength Elements:	E-Glass Yarns
Total Number of Tubes:	8
Number of fibers:	96
Waterblocking:	Dry Waterblocking
Rip-Cord:	Yes
Outer Jacket Color:	Turquoise
Marking:	Teldor Standard

Standards

Applicable Standards:	IEC 60794-1-21/22, IEC 60794, ISO/IEC 11801-1, TIA/EIA-568, RoHS 3 2015/863/EU
Flammability Rating:	IEC 60332-1, IEC 60332-3 , IEC 60754-2, IEC 61034, EN 50575:2014 Dcas1d1a1 (CPR)
Installation:	Guidelines as per IEC TR 62691

Performance

Max. Installation Tensile Load :	2700 N max.
Max. fiber strain at MIT:	0.6 %
Max. Residual Tension (MRS) :	810 N max.
Max. Fiber Strain at MRS.:	0.2 %
Impact Resistance:	10 N*m
Impact Resistance:	3 cycles
Max. Crush Resistance:	400 N/cm
Min. Bend Radius for Installation:	20xD mm
Min. Bend Radius for Operation:	10xD mm
Repeated Bending:	25 cycles
Torsion (L=125 x d):	10 cycles
Max. Operating Temperature:	+75 °C
Min. Operating Temperature:	-40 °C
Max. Installation Temperature:	+45 °C
Min. Installation Temperature:	-20 °C
Max. Storage Temperature:	+75 °C
Min. Storage Temperature:	-40 °C
UV Resistance:	Yes
Waterblocking:	Yes

Prepared By	Revised By	Version Num	Modified on
Zuri Balal	David Miller	1.4	01-10-2020

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd. - Ein-Dor, 1933500 ISRAEL Tel: +972 4 6770555 Fax: +972 4 6770650